

Alsecco-Dämmflex

Joint sealing compound for sealing connection joints



AREAS OF APPLICATION

Joint sealing compound for the permanent sealing of connection joints in the alsecco facade systems.

PRODUCT PROPERTIES

- Quickly rainfast
- Compatible with paint coats
- Plastoelastic
- High resilience
- Quick and easy application because only one component

TECHNICAL DATA

Binder base	Acrylic dispersion
Specific gravity	approx. 1,6 g/cm ³

APPLICATION INSTRUCTIONS

Preparation	Mask connecting areas, to establish neat joints.
Substrate pre-treatment	All substrates must be stable, clean and free of any residue, which can reduce adhesiveness. Substrates can be moist but not wet.
Application	Inject Dämmflex into the prepared joint using a spray gun and swipe smooth with brush and water. Only insert as much joint sealer as can be swiped smooth before skin begins to form.
Consumption	approx. 50 - 150 ml/m connection joint (depending on cross-section) Determine the precise material requirements by means of a trial coating on the object.
Information about the weather	Temperatures below + 5 °C may not arise during application and drying.

Drying time	approx. 5-20 days
	Depending on joint size, temperature and relative humidity, in the event of unfavourable weather conditions even longer.
Cleaning of tools	In a fresh state with water.

STORAGE

Shelf life in original sealed packaging of at least 1 year when kept cool and protected against frost.

PACKAGING INFORMATION

Colour	White
Packaging unit	Bag approx. 400 ml

OTHER INFORMATION

Information on safety	The information provided in the current safety data sheet applies.
Transportation	Not a hazardous material
Giscode	M-DF02 latex paints

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ